



Main

Range	Asfora
Product or component type	USB charger
Number output current	2.4 A
Integrated connection type	2 USB 2.0 port 5 V DC 2.4 A

Complementary

Device application	Charger
Device mounting	Flush
Device presentation	Mechanism with fixing frame
Colour tint	Anthracite
Surface treatment	Untreated
Fixing mode	By claws By screws
Type of packing	Flow-pack
[Ue] rated operational voltage	100...240 V AC +/- 10 % 50/60 Hz
Power consumption in W	0,075 W
Nominal output power	12 W
Input power	12 W
Service life in hours	30000 h 12 W
Material	ABS (acrylonitrile butadiene-styrene) centre plate PC (polycarbonate) GF10 FR casing PC (polycarbonate) GF10 FR internal cover
Protection type	Short-circuit protection
Number of terminals	2 screw terminals
Clamping connection capacity	2 x 0.75...2 x 2.5 mm ² rigid 2 x 0.75...2 x 2.5 mm ² flexible 2 x 0.75...2 x 2.5 mm ² stranded
Wire stripping length	8 mm
Product compatibility	Mobile/Tablet Mac iOS Mobile/Tablet Android Mobile/tablet Windows
Height	45 mm
Width	22,5 mm
Depth	42 mm
Embedding depth	30,8 mm

Environment

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	EN 62684 EN 60950-1 ETSI EN 301 489-4
Directives	2006/95/EC - low voltage directive 2004/108/EC - electromagnetic compatibility
Product certifications	EAC
Electrical insulation class	Class II
IK degree of protection	IK04
IP degree of protection	IP20

Pakavimo vienetai

Pirmos pakuotės vieneto tipas	PCE
Vienetų skaičius 1 pakuotėje	1
1-os pakuotės aukštis	7,1 cm
1-os pakuotės plotis	7,1 cm
1-os pakuotės ilgis	4,3 cm
1-os pakuotės svoris	81,0 g
Antros pakuotės vieneto tipas	S02
Vienetų skaičius 2 pakuotėje	24
2-os pakuotės aukštis	15,0 cm
Package 2 Width	30,0 cm
2-os pakuotės ilgis	40,0 cm
2-os pakuotės svoris	1,949 kg

Offer Sustainability

REACH direktyva	REACH Deklaracija
ES RoHS direktyva	Atitinka ES RoHS Deklaracija
Be gyvsidabrio	Taip
Kinijos RoHS direktyva	Kinijos RoHS Deklaracija
RoHS išimčių informacija	Taip